

KCS TOPIQ® EFFICIENT PRO

	Board	Tegula 24/90	Tegula 15/90														
 Kantdetaljer Yderligere kantdetaljer på forespørgsel																	
 Tykkelse (mm)	20	20	20														
 Mål (mm) Flere størrelser på forespørgsel	600 x 600 625 x 625 1200 x 600	600 x 600 625 x 625 1200 x 600	600 x 600 625 x 625 1200 x 600														
 System	Synligt demonterbart – System C																
 Vægt	2,8 kg/m ²																
 Farve	Hvid																
 Lydabsorption	DS/EN ISO 354 $\alpha_w = 1,00$ iht. DS/EN ISO 11654 – Klasse A <table border="1" data-bbox="647 1010 1278 1084"> <thead> <tr> <th>Frekvens f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_p</td> <td>0,45</td> <td>0,90</td> <td>1,00</td> <td>0,95</td> <td>1,00</td> <td>1,00</td> </tr> </tbody> </table> NRC = 0,95 iht. ASTM C 423			Frekvens f (Hz)	125	250	500	1000	2000	4000	α_p	0,45	0,90	1,00	0,95	1,00	1,00
Frekvens f (Hz)	125	250	500	1000	2000	4000											
α_p	0,45	0,90	1,00	0,95	1,00	1,00											
 Lydisolering rum til rum	DS/EN ISO 10848-2 $D_{n,f,w} = 25$ dB iht. DS/EN ISO 717-1 CAC = 25 dB iht. ASTM E 413-10																
 Lydreduktion	DS/EN ISO 10140-2 $R_w = 15$ dB iht. DS/EN ISO 717-1																
 Brandreaktion	Euroklasse A1 iht. DS/EN 13501-1 RUS KM2 (G1, V1, D1, T1) iht. 123-FZ																
 Lysreflektion	88%																
 Fugtmodstand	100% relativ luftfugtighed																
 Renrum	ISO 4 iht. DS/EN ISO 14644-1																
 Indendørs luftkvalitet	   																
 Rengøring	  																
 Bæredygtighed	    																